TOOLS FOCUS NEW TO RANGE WORKSHOP ESSENTIALS

MARCH 2022

AST

Designers and manufacturers of Automotive Special Service Tools

AST5174

DIESEL 1.4 / 1.6 / 2.0 TDI (EA288) COMMON RAIL (BELT) ENGINE VALVE TIMING CHECK KIT - VAG

AST5174 contains the tools required for checking and setting the engine valve timing in the correct position.

Models: **Audi**: A1/A1 Sportback, A3 Cabrio, A3 Saloon, A3/A3 Sportback, A4, A4 Allroad, A4 Quatro, A5 Cabriolet, A5 Coupe, A5 Sportback, A6, Q5, S5 Coupe, TT • **Seat**: Alhambra, Ibiza, Leon/ST • **Skoda**: Fabia III Estate, Octavia III, Rapid/Spaceback, Yeti/Yeti Outdoor • **VW**: Beetle/Coccinelle/Maggiolino, Caddy/Caddy Maxi, CC, Golf Alltrack, Golf Cabrio, Golf SV/Sportsvan, Golf VII/Estate, Jetta, Passat, Passat Alltrack, Polo, Scirocco, Sharan, Touran, Transporter T6

Equivalent to OE References: T10060A, T10490, T10492, VAG3359

AST6184

FUEL FILTER HOUSING WRENCH - 2.5TDI VOLKSWAGEN - 2.0D / 2.4D VOLVO

AST6184 Fuel Filter Wrench is suitable for the removal and installation of the filter housing cap to facilitate the replacement of the fuel filter cartridge fitted to 2.5TDi Volkswagen and 2.0 / 2.4 Volvo diesel engines.

Typical Applications: **Volvo**: C30, C70, S40, S60, S80, V50, V60, V70, XC60, XC70, XC90 • **VW**: Crafter (2006-2013) AUH, BC0, BJJ, BJK, BJL, BJM, CEBA, CEBB, CECA, CECB

Equivalent to OE References: 999-7084, T50011

AST6165

UNIVERSAL LOCKING WHEEL NUT/BOLT REMOVAL KIT

AST6165 provides a method of removing locking wheel nuts / bolts when the specialist key is not available.

Simple operation: Select one of the 5 adaptor sizes from the kit, locate the adaptor on the head of the bolt and use the supplied impact driver to release the locking wheel bolt.

Suitable for McGard style locking wheel nuts and bolts. AST6165 contains 3 double ended keys that can be formed to suit the profile of the locking wheel nut/bolt.

AST6156

DOUBLE ENDED WHEEL NUT/BOLT SOCKET - 18.5mm/19.5mm

AST6156 Double Ended Wheel Nut / Bolt Socket features 18.5mm and 19.5mm hex forms for the removal of damaged wheel nuts / bolt.

Features 18.5mm and 19.5mm oversize hex forms • Designed for the removal of 19mm chrome capped wheel nuts/bolts where the chrome cap is missing or damaged • Undersized and Oversized hex form provides a secure fit around the fastener to enable removal from the vehicle • Suitable for chrome covered wheel nuts / bolts commonly seen on **Chrysler**, **Jeep**, **Lexus**, **Toyota** and **Volvo** models • Used in conjunction with a 1/2" extension bar (not included)



+44 (0)1527 522550

